

Screw-In Thermowells (909710)

- For thermocouples and RTD temperature probes
- Thermometers can be replaced without draining the system
- For operating temperatures up to 400 °C
- Produced from stainless steel 1.4571



Order details

(1) Basic type			
	909710/10	Screw-in pocket, cylindrical, with female thread G 1/2 (similar to DIN 16179 Form D)	
	909710/11	Screw-in pocket, cylindrical, with female thread G 1/2 (DIN 16179 Form D)	
		(2) Operating temperature in °C	
X	X	848	0..400°C
		(3) Protection tube diameter	
X		8,0	Outer diameter 8mm / inner diameter 6,2mm
	X	13,0	Outer diameter 13mm / inner diameter 11mm
		(4) Probe fitting length	
X	X	100,0	100mm
X		150,0	150mm
	X	160,0	160mm
X	X	250,0	250mm
		(5) Process connection	
X	X	104	Screw connection G 1/2
		(6) Protection tube material	
X	X	26	Stainless steel 316 Ti (material-no. 1.4571)
		(7) Extra codes	
X	X	0000	Without extra code
X	X	1160	H2 ready - mobile hydrogen applications

Order code

(1)	(2)	(3)	(4)	(5)	(6)	(7)

Quantity discounts upon request



Stock versions

Order code	Part no.
909710/10-848-8-100-104-26/000	00489140
909710/10-848-8-150-104-26/000	00489141
909710/10-848-8-250-104-26/000	00531795
909710/11-848-13-100-104-26/000	00044862
909710/11-848-13-160-104-26/000	00044863
909710/11-848-13-250-104-26/000	00044864