

JUMO dTRANS T06 Ex – Multifunctional Four-Wire Transmitter in Mounting Rail Case with SIL and Ex Approval (707075)

- Universal input for a large number of sensors and standard signals
- SIL 2/SIL 3 according to DIN EN 61508 and PL c/d according to ISO 13849
- Reliable operation through sensor monitoring and hardware error detection
- ATEX and IECEx approval
- Customer-specific linearization
- Intuitive operation and configuration on the device or via USB interface with setup program
- RS485 interface (option)
- Intelligent additional functions such as min./max. drag indicator, operating hours counter, and output simulation
- Connection diagram can be viewed in the LCD display



Order details

(1) Basic type	
707075	JUMO dTRANS T06 Ex
(2) Version	
8	Standard with default settings
9	Customer-specific configuration (specification in plain text)
(3) Voltage supply	
29	DC24V +10/-15 %
(4) Extra codes	
000	Without extra code
053	Interface RS485 galvanically isolated

Order code

(1)	(2)	(3)	(4)
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>



Stock versions

Order code	Part no.
707075/8-29/000	00731091
707075/8-29/053,	00729720

Accessories

Description	Part no.
USB cable, A connector to Micro-B connector length 3 m	00616250
Screw-on end clamp for mounting rail	00528648
Connector 4pol black (51-54) Steckerteil	00771256

Software

Description	Part no.
SETUP Programm JUMO dTRANS T06 LCD/Ex	00668006